

## OMEGA FIX PRIMER

### DESCRIPTION

Water born impregnation primer based on acrylic copolymer and Formulated to provide deep penetration into masonry type surfaces.

### PRINCIPALS CHARACTERSTICS

- For interior use.
- Very Good sealing properties.
- Excellent foundation coat .for various emulsion systems.
- Good adhesion properties.
- Good Penetration.
- Unsabonfiable.
- Quick drying.
- Easy to apply.
- Environmentally friendly.

### COLOR AND GLOSS LEVEL

- White.
- Flat

### BASIC DATA AT 20°C (68°F)

Data for product	
Mass density	1.35 kg/l
Volume solid	22.7 ±2 %
Theoretical spreading rate	8 m <sup>2</sup> /l @30µm DFT depending on the nature , condition of the substrate and application method employed
Touch dry after	Approx. 30 minutes depending on the thickness
Over coating interval	Min 6 hours Max -no limitation
Shelf life	24 months
Flash point	Above 65°C



## OMEGA FIX PRIMER

---

### Recommended substrate conditions

Substrate must be dry and free from laitance and any other contamination

### System specification

- Fix Primer to seal and reduce the porosity of substrates
  - Suitable for interior application to plaster ,brickwork ,concrete, rendered surfaces and the majority of cement type building surfaces
  - Priming coat in emulsion systems
- 

### Instruction for use

<b>Application Methods</b>	<b>Brush &amp; Roller</b>
<b>Recommended thinner</b>	Sweet Water
<b>Volume of thinner</b>	5 – 10%

### SAFETY PRECAUTIONS

Follow Safety & Healthy Environmentally Precautions  
Complies with Environmental specifications

### REFERENCES

For more technical information's don't hesitate to contact technical department

