

DESCRIPTION

Road and pavement marking paint based on modified binder (As per Egyptian organization and standardizations No 794/2007).

PRINCIPALS CHARACTERSTICS

- For interior & exterior use.
- Unsabonfiable.
- Develop to give good adhesion to concrete and asphalt.
- Excellent abrasion resistance.
- Excellent hiding power.
- Good resistance water and oil.
- quick draying.
- Easy to apply.

COLOR AND GLOSS LEVEL

- White, Yellow and Black.
- Flat

BASIC DATA AT 20°C (68°F)

Data for product	
Mass density	1.4 kg/l
Volume solid	50 ±2 %
Theoretical spreading rate	5 m ² /l @100µm depending on the nature , condition of the substrate and application thickness
Touch dry after	Approx. 10 minutes
Over coating interval	Min 16 hours Max -no limitation
Shelf life	12 months
Flash point	Above 7°C

Recommended substrate conditions and temperatures

- concrete must be drying sufficiently dry and free from dirt
 - Greases, laitance and any other contamination.
 - Asphalt surfaces must be free from any contaminations.
-

System applications

- quick draying paint to be applied in one coat forking lines and pattern on concrete and asphalt surfaces.
-

Instruction for use

Air SPRAY

Recommended thinner	Thinner No 21
Volume of thinner	5 – 10 %
Nozzle Orifice	approx. 2 – 3mm

BRUSH & ROLLER

Recommended thinner	No Thinner to be added
Volume of thinner	roller and brush application is not recommended for asphalt surfaces

<u>CLEANING SOLVENT</u>	Thinner No 21
--------------------------------	---------------

SAFETY PRECAUTIONS

Follow Safety &Healthy Environmentally Precautions **Complies** with Environmental specifications

REFERENCES

For more technical information's don't hesitate to contact technical department